

Nasiff Associates, Inc. is the FIRST and continues to take the lead in PC-Based Resting ECG Systems.

A true 12- lead interpretive ECG with the ability to perform USB and Bluetooth ECG testing from the same device depending on your needs.

Performing fast testing and managing them easily with you at the point-of-care.

- Performs ECG tests on PC/laptops, MAC (PC/laptops) and mobile devices. (WINDOWS TABLETS, Android cell phones and tablets)
- Cardio Universal EMR Interface™ pdf, bidirectional Dicom, bidirectional HL7 and all standard interfaces...
- Cardio Patient Data Management™ System
- Built-In Networking with an Unlimited Patient Database
- Legendary quality, excellent customer support and training
- Reliable, user-friendly, compact and durable devices
- Feature rich at the best price
- Advanced security features with password options
- Made in USA
- FDA Clearance since 1990





## Nasiff Cardio Card® RESTING DUAL CONNECTIVITY ECG SYSTEM

## **SPECIFICATIONS**

CONNECTION WITH PC	USB and Bluetooth connection	life or
POWER SUPPLY	USB DC 5v or two AA batteries	
POWER CONSUMPTION	< 200mA from USB or batteries	
COMPARISONS	ECG/EKG serial historical comparisons	
ECG MEASUREMENT RESOLUTIONS	2-4 msec, 1.22uV at 10mm/mV gain	45.4
HEART RATE RANGE	30-300bpm	Unable of cust captured with about of the prince and the first of the
LEADS	Standard 12- lead	was a second of the second
LEAD LEAKAGE	< 10uA	of it is a second of the second
ACQUISITION MODE	Simultaneous interpretive 12- lead acquisition	
SAMPLING RATE	12- lead sampling rate 250-1000Hz	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
A/D RATE	1kHz	the same of the sa
TIME BASE	12.5, 25 and 50 mm/sec	100 100 100 100 100 100 100 100 100 100
DYNAMIC RANGE	± 5 mV	was seen as seen as the seen a
FREQUENCY RESPONSE	0.05 to 150 Hz (higher available)	The same of the sa
GAINS	2.5, 5, 10, 10/5, 20, 40 mm/mV	
INPUT IMPEDANCE	>10 <sup>12</sup> ohms	
SYSTEM NOISE	<40 uV RTI	
ECG INTERPRETATION CLASSES	Mls, blocks, enlargements, axis and AFib	Promise poor
FILTERS	AC, baseline, muscle artifact	Marketine Ball a Market
CMRR	>120 dB	mhilahahaha in in in in in in
NETWORKING	Built-in	In 18 SIAM, & Bosson/KAACSbend 13.
MEASUREMENTS	HR with global measurements, complete interval	values

and ST information

0.26 lb (0.12 kg)

Dual Boot, VMware Fusion or Parallels

ORDERING INFORMATION CardioResting Dual System — CC-ECG1-DBT

**CPT CODE 93000** (additional codes: 93005; 93010)

FOR MORE INFORMATION CONTACT:

**DIMENSIONS** 

**WARRANTY** 

**PC REQUIREMENTS** 

**WEIGHT** 

Nasiff Associates, Inc. 841-1 County Route 37, Central Square, NY 13036 phone: 315.676.2346 • fax: 315.676.4711 • toll-free: 866.NASIFFA (866.627.4332) tech support: 315.676.2346 • email: sales@nasiff.com • web: www.nasiff.com



2.75" W x 1.25" D x 4.87" H (6.985 cm x 3.175 cm x 12.364 cm)

Tablet/Laptop/Desktop PC, Intel Compatible, 4GB RAM, 40GB HD, WINDOWS XP through WINDOWS 7, 8, 10 and MAC's with Boot Camp,

Two-year limited manufacturer's warranty, support and training

